



LED LINK
T E C H N O L O G Y

LED Lighting Catalogue

Greenhouses



Poultry Farms



Growth plant



LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr

info@ledlink.gr



LED LINK
T E C H N O L O G Y

Lighting Fixture for Plant Growth

LL Delta 1,20



Body: DKP Sheet Steel Sheet

Painting: Electrostatic

Ingress Protection: IP54

Color code: RAL9016

Base Lamp holder: G13

Type Lamp: T8 LED TUBE Plant Growth

Voltage	Electrostatic Connection	Type LED	CRI	Warranty
AC220 - 240V 50-60 Hz	Single-Side	SMD	>80	1 year

EN 60598-2-1



LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr

info@ledlink.gr



LEDLINK
TECHNOLOGY

Lighting Fixture for Plant Growth

LL Alpha 1,20



Body: Metallic

Painting: Electrostatic

Ingress Protection: IP20

Color code: RAL9016

Base Lamp holder : G13

Type Lamp: T8 LED TUBE Plant Growth

Voltage	Electrostatic connection	Type LED	CRI	Warranty
AC220 - 240V 50-60 Hz	Single-Side	SMD	>80	1 year

CE EN 60598-2-1

LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr

info@ledlink.gr




LEDLINK
TECHNOLOGY

Poultry light with IP 65 (waterproof, dustproof)

LL Poultry Led



Beam Angle	Product Code	Power	Voltage	Luminus Flux	CCT	Dimensions
120°	LL POULTRY 36/3000	36W	200-240VAC	110-120Lm/W	3000K	A=1200mm B=1144-1147mm C=75mm
	LL POULTRY 36/4000	36W	200-240VAC	110-120Lm/W	4000K	
	LL POULTRY LED 3000 DIMMABLE	36W	200-240VAC	110-120Lm/W	3000K	
	LL POULTRY LED 4000 DIMMABLE	36W	200-240VAC	110-120Lm/W	4000K	

Product Code	Tube	Mechanical Protection	Ingress Protection	CRI	Warranty
Led poultry light 36W	Milky	IK10	IP69	≥80	5 years



LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr

info@ledlink.gr



LEDLINK
TECHNOLOGY

Lighting Fixture 2xT8 Led Tube with IP65



Product Code	Body	Type Lamp	Dimensions
LL FIXTURE-218/B	Plastic	2 X T8 9W (not included)	L667XW150XH106m
LL FIXTURE-236/B	Plastic	2 X T8 18W (not included)	L1264XW150XH110mm
LL FIXTURE-258/B	Plastic	2 X T8 23W (not included)	L1560XW147XH62m

Warranty	Supply	Type Lamp	Ballast	Ingress Protection
2 years	Wall or suspended	T8	No	65



LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629





www.ledlink.gr

info@ledlink.gr



LEDLINK
TECHNOLOGY

Lighting Fixture 2xT8 IP66 Premium
LL T8 Waterproof Premium Fixture



Body: Galvanized steel

Painting: Electrostatic anti-UV painting with high rust resistance.


Ingress Protection: IP65

Clips: INOX


Base (Lamp holder): G13

Lamp Type: T8 LED TUBE (not included)

140°



100% Resistance at test of 500-hour spray with NaCl.



LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr

info@ledlink.gr



LEDLINK
TECHNOLOGY

Led Lamp T8 Tube



Voltage	Colour Temperature	Type LED	CRI	Beam Angle	Lifetime
AC165-265V	3000K -4500K -6500K	SMD2835	>80	180 °	40.000 hours

Product Code	Cover	Power	Lumen	Dimensions
LL-Tube-T8 0,60	Milky	10W	1000lm	Φ26 x 600mm
LL-Tube-T8 1,20	Milky	20W	2000lm	Φ26 x 1200mm
LL-Tube-T8 1,50	Milky	25W	2500lm	Φ26 x 1500mm

*** Isolated Drivers**



LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr

info@ledlink.gr



LEDLINK
TECHNOLOGY

Led Lamp T8 Plant Growth



Voltage/ Frequency	Colour Temperature	Material	CRI	warranty	Lifetime
AC220-240V 50-60 Hz	Full Spectrum	Glass	>80	2 years	25.000 hours

Product Code	Connection	Power	Lumens	Ingress Protection	Dimensions
LL-Tube-T8 1,20	Single - Side	18W	2000lm	IP65	Φ26 x 1212mm

*** Isolated Drivers**



EN 60598-2-1



LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr

info@ledlink.gr



LEDLINK
TECHNOLOGY

Floodlight LED SMD Regular



Voltage	Color Range	Type LED	CRI	Beam Angle	Warranty	Lifetime
AC 85-265V	3000-6500K	SMD	>80	120 °	1 Year	25.000 hours

Product Code	Power	Replacement	Lumen	Dimensions
LL SMD-111-10W	10W	40W	950	128X120X48mm
LL SMD-111-20W	20W	80W	1900	168X160X50mm
LL SMD-111-30W	30W	120W	2850	228X222X53mm
LL SMD-111-50W	50W	250W	4750	288X279X63mm
LL SMD-111-100W	100W	400W	9500	290X90X340mm
LL SMD-111-150W	150W	600W	14250	335X95X390mm
LL SMD-111-200W	200W	800W	19000	335X95X390mm




LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr
info@ledlink.gr



LEDLINK
TECHNOLOGY

LL Led Floodlight Stadium



Body Material: Aluminium

Driver efficiency: PF 0,9

Τύπος LED: SMD

Warranty: 3 years

Product Code	Power	CRI	Lumen
LL FloodLight Stadium-4x50W	200W	≥80	26.000



Voltage Stabilizer
is recommended

LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr

info@ledlink.gr



LEDLINK
TECHNOLOGY

Floodlight LED Carol Premium




Body: Anodized Aluminium

Driver Efficiency: PF 0,9

LED Type: Modules with lens

Description	Power	Lumen	Dimensions
LL-Carol1 1x50W	50W	159/watt	190X145X35mm
LL- Carol2 2x50W	100W	159/watt	190X290X35mm
LL- Carol3 3x50W	150W	159/watt	190X435X35mm
LL-Carol4 4x50W	200W	159/watt	380X290X35mm

Voltage	Colour Temperature	Ingress Protection	CRI	Warranty	Lifetime
AC 220 -240V	3000-6500K	IP66	>80	4 years	50.000 hours



Class of Insulation: II- Conforms to the standard EN 60598-1 EN 62031

LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr

info@ledlink.gr



LEDLINK
TECHNOLOGY

Street Lighting

LL LED StreetLight PER



Body: Aluminum.

Driver efficiency: PF 0,9

LED: EPISTAR

Colour: Graphite

Voltage	Colour Temperature	Power	CRI	Lumens	Beam Angle
AC220 -240V	5000K	60W	80	8.400	140°
AC220 -240V	5000K	90W	80	12.600	140°
AC220 -240V	5000K	120W	80	16.800	140°
AC220 -240V	5000K	150W	80	21.000	140°



Voltage Stabilizer
is recommended

LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr

info@ledlink.gr



LEDLINK
TECHNOLOGY

LEDLINK TECHNOLOGY 68 Chr.Smirnis, 18540 Piraeus (+30)210 4126629

www.ledlink.gr

info@ledlink.gr